



(12)

EUROPEAN PATENT APPLICATION

(21) Application number : **92300185.3**

(51) Int. Cl.⁵ : **H04B 1/40**

(22) Date of filing : **09.01.92**

(30) Priority : 11.01.91 JP 2291/91
11.01.91 JP 2294/91
11.01.91 JP 2297/91
11.01.91 JP 2298/91
11.01.91 JP 2299/91

(43) Date of publication of application :
15.07.92 Bulletin 92/29

(84) Designated Contracting States :
DE FR GB SE

(71) Applicant : **KABUSHIKI KAISHA TOSHIBA**
72, Horikawa-Cho Saiwai-ku
Kawasaki-shi Kanagawa-ken (JP)
(71) Applicant : **TOSHIBA COMMUNICATION**
TECHNOLOGY CORPORATION
3-1-21 Asahigaoka
Hino-shi, Tokyo (JP)

(72) Inventor : **Marui, Kuniyoshi, c/o Intellectual Property**
Div.
Toshiba Corporation, 1-1-1, Shibaura
Minato-ku, Tokyo (JP)
Inventor : **Sato, Goichi, c/o Intellectual Property Div.**
Toshiba Corporation, 1-1-1, Shibaura
Minato-ku, Tokyo (JP)
Inventor : **Ishii, Takaaki, c/o Intellectual Property**
Div.
Toshiba Corporation, 1-1-1, Shibaura
Minato-ku, Tokyo (JP)
Inventor : **Takachi, Shinji, c/o Intellectual Property**
Div.
Toshiba Corporation, 1-1-1, Shibaura
Minato-ku, Tokyo (JP)
Inventor : **Sawa, Buntaro, c/o Intellectual Property**
Div.
Toshiba Corporation, 1-1-1, Shibaura
Minato-ku, Tokyo (JP)
Inventor : **Sato, Hiroshi, c/o Intellectual Property Div.**
Toshiba Corporation, 1-1-1, Shibaura
Minato-ku, Tokyo (JP)

(74) Representative : **BATCHELLOR, KIRK & CO.**
2 Pear Tree Court Farringdon Road
London EC1R 0DS (GB)

(54) **An adapter unit for adaptively supplying a portable radio telephone with power.**

(57) A portable radio unit (200) used with an adapter unit (1) having a hands-free circuit (70) and for adaptively supplying the portable radio unit with electric power. The hands-free circuit is activated in response to a contact between a connector (T92, T62) of the portable radio unit and a connector (T91, T61) of the adapter unit in the event that the portable radio unit is in a communication state when it is attached to the adapter unit. When the portable radio unit is not powered by its rechargeable battery (100) attached thereto or is not in a communication state when it is connected to the adapter unit, the first power supply circuit (40) of the adapter unit supplies the rechargeable battery of the portable radio unit. When the portable radio unit is in the communication state when it is connected to the adapter unit, the second power supply circuit (30) of the adapter unit supplies the portable radio unit through the rechargeable battery.

This invention relates to the field of the radio telephone apparatus such as cellular radio telephones and cordless telephones and, more particularly, to an improved portable radio telephone apparatus which can be coupled to an adapter unit.

As cellular radio telephone come into wide use, various types of vehicle adapters have been developed. For example, U.S. patent 5,048,117 to Aisaka et al discloses an adapter unit which may amplify radio frequency signals output from a portable radio telephone in response to a level control signal. As another example of the vehicle adapter, U.S. patent application serial no. 07/249,817, filed September 27, 1991 entitled "Radio Telephone Apparatus" discloses a radio telephone apparatus wherein a portable radio device may be connected to an additional unit have a speaker and a microphone via a cable, so that hands-free operations become available to the user of the apparatus when they are connected to each other. By means of these types of adapter, a user may have a telephone conversation with hands-free operation.

According to such conventional adapters, however, the user has to first connect the portable unit with the adapter unit by means of the cable and turn both of them on before hands-free operation is possible. In addition with conventional adapters, two power supply lines are required in a connection cable between the portable radio telephone and the adapter unit; one for charging the battery of the portable radio telephone and the other one for supplying the portable radio telephone with electric power. This increases the required number of components for the portable radio telephone. Furthermore, an adapter capable of connecting the portable radio telephone with a data transmission apparatus such as a facsimile has not been possible.

It is accordingly an object of the present invention to provide an improved radio telephone apparatus having a portable radio unit and an adapter unit which can provide hands-free operation when the portable radio telephone is installed in the adapter unit.

It is another object of the present invention to provide an improved radio telephone apparatus having a portable radio unit and an adapter unit, wherein only one power supply line is needed for supplying the portable radio telephone with electric power from the adapter unit.

It is still another object of the present invention to provide an improved radio telephone apparatus having a portable radio unit and an adapter unit, wherein the adapter unit may be connected to a data communication device such as a facsimile machine so that the data supplied from the data device is transmitted to or from the portable radio telephone.

In accordance with the present invention there is provided a radio telephone apparatus comprising a portable radio unit having receiving means for receiv-

ing radio frequency signals, demodulating means coupled to the receiving means for demodulating the radio frequency signals into audio signals, an ear-piece coupled to the demodulating means for outputting the audio signals, a mouthpiece for inputting speech signals, modulating means coupled to the mouthpiece for modulating the speech signals into radio frequency signals, transmitting means coupled to the modulating means for transmitting the radio frequency signals, and an adapter unit attachable to the portable radio unit, having a speaker, a microphone and a hands-free circuit coupled to the second contact type connector means, the speaker, and the microphone for controlling the level of signals output from the speaker in response to the level of signals input to the microphone, characterised by:

first computer means on the possible unit and co-operating second connector means on the adapter, whereby the hands-free circuit is activated in response to a contact between the first connector means and the second connector means in the event that the portable radio is attached to the adapter unit whilst communication is in progress.

Thereby, a user of the portable radio unit who has had a conversation with another party over a radio link using the portable radio unit may enter a hands-free conversation while continuing the conversation only by mounting the portable radio unit on the adapter unit.

Preferably, the radio telephone apparatus is further characterised in that the hands-free circuit is not activated in response to a contact between the first contact type connector means and the second contact type connector means unless the portable radio unit is powered up when it is attached to the adapter unit.

preferably the radio telephone apparatus is further characterised in that the portable radio unit comprises first power supply means for charging a rechargeable battery of the portable radio unit in the event that the portable radio unit is connected to the adapter unit when it is not being used for communication and second power supply means for supplying the portable radio unit with electric power in the event that the portable radio unit is attached to the adapter unit when it is communicating. The power supply capacity of the second power supply means is larger than that of the first power supply means.

Preferably, the radio telephone apparatus is further characterised in that the adapter unit comprises a terminal for connecting an external data device with the adapter, and switch means responsive to a control signal for connecting the terminal to the second contact type connector means, whereby a two-way data transmission path is established between the external data device and the portable radio unit when the portable radio unit is connected to the adapter unit.

In accordance with another aspect of the present invention, an adapter unit used with a portable radio unit coupled to the adapter unit and having a rechargeable battery for supplying the portable radio unit with electric power, is characterised in that the adapter comprises first power supply means for charging the rechargeable battery with electric power in the event that the portable radio unit is not powered by the rechargeable battery when it is connected to the adapter unit and second power supply means for supplying the portable radio unit with electric power in the event that the portable radio unit is being powered by the rechargeable battery and in a communication state when it is attached to the adapter unit. The power supply capacity of the second power supply means is larger than that of the first power supply means. Thereby, the portable radio unit may be fed with the adapter unit via a unique power supply line when the portable radio unit is attached to the adapter unit.

Preferably, the adapter unit is further characterised in that the adapter unit comprises a hands-free circuit for controlling the level of signals output from a speaker of the adapter unit in response to the level of signals input to a microphone of the adapter unit.

Preferably, the adapter unit is further characterised in that the hands-free circuit is activated in response to a connection between the adapter unit and the portable radio unit when it is in a communication state.

Preferable, the adapter unit is further characterised in that the hands-free circuit is not activated in response to a connection between the adapter unit and the portable radio unit when it is not in the communication state.

Preferably, the adapter unit is further characterised in that the adapter unit comprises a terminal for connecting an external data device with the adapter, and switch means responsive to a control signal for connecting the terminal to a first contact type connector means, whereby a two-way data transmission path is established between the external data device and the portable radio unit in response to a contact between the first contact type connector and a second contact type connector of the portable radio unit in the event that the portable radio unit is attached to the adapter unit.

Some embodiments of the invention will now be described by way of example with reference to the accompanying drawings in which:

Figure 1 is a block diagram showing an embodiment of an adapter for radio telephone equipment according to the present invention;

Figure 2 is a block diagram of the adapter of Figure 1;

Figure 3 is a block diagram showing in detail a hands-free circuit section of the adapter of Figure 1;

Figure 4 is a circuit diagram showing in detail a battery pack of the adapter of Figure 1;

Figure 5 shows a terminal signal of a portable radio telephone of the adapter of Figure 1;

Figure 6 shows the external appearance of a radio telephone equipment to which the present invention is applied;

Figure 7 is a block diagram shown in detail a portable radio telephone according to the embodiment of Figure 1.

Figure 1 shows the overall arrangement of a cellular portable radio telephone according to an embodiment of the present invention. The radio telephone comprises an adapter 1, and a portable radio telephone 200 and a battery pack 100 both of which are detachable connected to the adapter 1 through a contact type connector 300. The battery pack 100 is detachably connected to the radio telephone 200 through a connector 400.

The adapter 1 comprises a power supply section 10 for a hands-free circuit section, a power supply control circuit section 20, a main power supply circuit section 30, a sub-power supply circuit section 40, an overcurrent detection/protection circuit section 50, and a hands-free circuit section 70. The power supply section 10 supply the hands-free circuit section 70 with electric power, and the power supply control circuit section 20 controls the main power supply circuit section 30 and the sub-power supply circuit section 40. The main power supply circuit section 30 is connected to a car mounting battery 500 at a terminal T_a to supply power to both the portable radio telephone 200 and battery pack 100 when the portable radio telephone 200 having established a radio link is connected to the adapter 1. The sub-power supply circuit section 40 supplies power for charging the battery pack 100 when the portable radio telephone 200 is its non-operating or reception-waiting state is connected to the adapter. The hands-free circuit section 70 is connected to a speaker 900 at a terminal T_d and also connected to a microphone 700 at a terminal T_c to enable a call using the speaker 900 and microphone 700 when the radio telephone is connected to the adapter 1. Further, the hands-free circuit section 70 may be connected at a terminal T_b to a data terminal such as a facsimile apparatus 600, and data communication can be performed using the data terminal. The adapter 1 may be mounted near the driver's seat in a car.

The contact type connector 300 includes nine pins to connect terminals T11, T21 and T31 on the power supply control circuit section 20 with terminals T12, T22 and T32 of the battery pack 100, respectively, and to connect terminals T41 and T51 of the power supply control circuit section 20 and terminals T61, T71, T81 and T91 of the hands-free circuit section 70 with terminals T42, T52, T62, T82 and T92 of the portable radio telephone 200 respectively. The

connector 400 includes two pins to connect terminals T111 and T121 of the battery pack with terminals T112 and T122 of the portable radio telephone 200.

Figure 2 shows the interconnection of the power supply section 10 for the hands-free circuit section, power supply control circuit section 20, main power supply circuit section 30, sub-power supply section 40, and overcurrent detection/protection circuit section 50. Figure 3 shows the interconnection of the hands-free circuit section 70. Figure 4 shows an arrangement of the battery pack 100. Figure 5 shows signals supplied to the terminals of the portable radio telephone 200.

The operations of the power supply section 10, power supply control circuit section 20, main power supply circuit section 40, and overcurrent detection/protection circuit section 50 will be described in detail with reference to Figure 2.

Since the operations of the power supply section 10, power supply control circuit section 20, main power supply circuit section 30, sub-power supply circuit section 40 and over current detection/protection circuit section 50 depend upon the operating state of the portable radio telephone 200, they will be described for each of the following three modes.

1. In the event that the portable radio telephone 200 of which power switch is turned off is connected to the adapter 1, the operations of the above sections depend upon whether the temperature of the battery pack 100 falls within a range of temperature of 0 to 45° at which a battery 102 (shown in Figure 4) of the battery pack 100 can be charged.

Temperature T of the battery pack 100 is detected by a thermistor 101 (shown in Figure 4) of the battery pack 100, and information representing the temperature T is supplied to the terminal T21 of the power supply control circuit section 20 through the contact type connector 300. The information supplied to the terminal T21 is converted into a voltage signal corresponding to the detected temperature T of the battery pack 100, and then transmitted to both a minus terminal of a comparator 21 and plus terminals of comparators 22 and 23.

The comparator 21 outputs a high-level signal when a reference voltage ref 1 corresponding to 0°C is applied to its plus terminal and the voltage signal corresponding to the detected temperature T of the battery pack 100 is at a temperature of 0 or more degrees. The comparator 21 outputs a low level signal when the detected temperature T represented by the voltage signal is at the other temperatures ($T < 0$).

The comparator 22 outputs a high level signal when a reference voltage ref 2 corresponding to 45°C is applied to its plus terminal and the voltage signal corresponding to the detected temperature T of the battery pack 100 is at a temperature of 45°C or less. The comparator 22 outputs a low level signal when the detected temperature T represented by the voltage signal is

at the other temperature ($T > 45^\circ\text{C}$).

The comparator 23 outputs a high level signal when a reference voltage ref 3 corresponding to the maximum usable temperature 60°C is applied to its plus terminal and the voltage signal corresponding to the detected temperature T of battery pack 100 is at a temperature of 60°C or less. The comparator 23 outputs a low level signal when the detected temperature T represented by the voltage signal is at the other temperature ($T > 60^\circ\text{C}$).

Assuming that the detected temperature T of the battery pack 100 is $0 \leq T \leq 45$, the signals output from the comparators 21 and 22 are both high in level, AND conditions of an AND circuit 24 are satisfied, and the AND circuit 24 outputs a high level signal. The high level signal is supplied to a constant current circuit 41 of the sub-power supply circuit section 40 to turn on the circuit 41. The current of the constant current circuit 41 is limited to a value, e.g. 120mA, enough to charge the battery 102 of the battery pack 100. The output current of the constant current circuit 41 is supplied to the battery 102 through the terminal T31, contact type connector 300, terminal T32 of the battery pack 100, and current limiting resistor 103, thereby charging the battery 102.

In this state, since a power switch 201 (shown in Figure 5) of the portable radio telephone 200 is turned off, a power-on signal output from the terminal T52 of the portable radio telephone 200 is low in level. This low level signal is thus supplied to the control terminal of the power supply section 10 via the terminal T52, contact type connector 300, and terminal T51 and accordingly the switch of the power supply section 10 is turned off. Since, therefore, power is not supplied to the hands-free circuit section 70, the hands-free circuit section 70 is rendered inoperative. Since the output signal of a 5V regulator 12 which is supplied with the output signal of the switch 11, is low in level, the AND conditions of the AND circuit 25 supplied with the low level signal are not satisfied, the output signal of the AND circuit 25 is low in level, and a constant current circuit 32 of the main power supply circuit section 30 supplied with the output signal of the AND circuit 25, is turned off.

When the detected temperature T of the battery pack 100 is less than 0°C, that is, when $T < 0$, an output signal of the comparator 21 is low in level and, in this case, the AND condition of the AND circuit 24 is not satisfied, an output signal of the AND circuit 24 is low in level, the constant current signal 41 of the sub-power supply circuit section 40 is turned off and no charging current is supplied to the battery 102 of the battery pack 100.

When the detected temperature T of the battery pack 100 exceeds 45°C, that is, when $T > 45^\circ$, an output signal of the comparator 22 is low in level and, in this case, the AND conditions of the AND circuit 24 are not satisfied, an output signal of the NAND circuit

24 is low in level, and the constant current circuit 41 of the sub-power supply circuit section 40 is turned off. No charging current is thus supplied to the battery 102 of the battery pack 100.

2. In the event that the portable radio telephone 200 which is turned off is connected to the adapter 1, if a power switch 201 (shown in Figure 5) of the portable radio telephone 200 is turned on, a power on signal output from the terminal T52 of the portable radio telephone 200 becomes high in level. This high level signal is supplied to the control terminal of the switch 11 of the power supply section 10 through the terminal T52, contact type connector 300, and terminal T51. The switch 11 of the power supply section 10 is thus turned on.

If the switch 11 of the power supply section 10 is turned on, a power supply voltage of 13.7V is applied to the hands-free circuit section 70, and a power supply voltage of 5V, which is generated by smoothing the output of the 5V regulator 12 by a ripple filter, is applied to the hands-free circuit section 70. The hands-free circuit section is thus rendered operative. The operation of the hands-free circuit section 70 will be described in detail later.

Since the portable radio telephone 200 is in the wait state, a calling/waiting signal output from the terminal T42 of the portable radio telephone 200 is low in level. This low level signal is supplied to the AND circuit 25 through the contact type connector 300 and terminal T41, so that the AND conditions of the AND circuit 25 are not satisfied, an output signal of the AND circuit 25 is low in level, and the constant current circuit 32 of the main power supply circuit section 30 is turned off.

If the detected temperature T of the battery pack 100 ranges from 0 to 45°C ($0 \leq T \leq 45$), both the output signals of the comparators 21 and 22 become high in level, the AND conditions of the AND circuit are satisfied, the constant current circuit 41 of the sub-power supply circuit section 40 is turned on, and the battery 102 of the battery pack 100 is charged with the output current of the constant current circuit 41.

When the detected temperature T of the battery pack 100 is less than 0°C. that is, when $T < 0$, an output signal of the comparator 21 becomes low in level. Therefore, the AND conditions of the AND circuit 24 are not satisfied, the constant current circuit 41 of the sub-power supply circuit section 40 is turned off, and the battery 102 of the battery pack 100 is not supplied with charging current. When the detected temperature T of the battery pack 100 exceeds 45°C, that is, when $T > 45^\circ\text{C}$, an output signal of the comparator 22 becomes low in level and, in this case, the AND conditions of the AND circuit 24 are not satisfied, the constant current circuit 41 of the sub-power supply circuit section 40 is turned off, and the battery 102 of the battery pack 100 is not supplied with charging current. This operation is the same as that of the case where

the power switch 201 of the portable radio telephone 200 is turned off and the portable radio telephone 200 is connected to the adapter 1.

3. In the event that the power switch of the portable radio telephone 200 which has been turned on and established a speech radio link is connected to the adapter 1, a calling/waiting signal supplied to the terminal T42 of the portable radio telephone 200 becomes high in level. This high level signal is supplied to the AND circuit 25 through the contact type connector 300 and terminal T42.

If the detected temperature T of the battery pack 100 is not more than 60°C, and falls within a range capable of using the radio telephone, an output signal of the comparator 23 is high in level, and this high level signal is supplied to the AND circuit 25.

Since the power switch 201 (shown in Figure 5) of the portable radio telephone 200 is then turned on, a power on signal output from the terminal T52 of the portable radio telephone 200 is high in level, the switch 11 of the power supply section 10 is turned on, and an output signal of the 5V regulator 12 is high in level. This high level signal is also supplied to the AND circuit 25.

Further, an inverted signal output from a flip-flop circuit 59 of the hands-free circuit section 70, which will be described in detail, is high in level. This high level signal is also sub-circuit 25.

Consequently, all the signal supplied to the AND circuit 25 are high in level and, in this case, the AND conditions of the AND circuit 25 are satisfied and a high level signal is output from the AND circuit 25. This high level signal is supplied to the control terminal of the constant current circuit 32 of the main power supply circuit section 30 and accordingly the constant current circuit 32 of the main power supply circuit section 30 is turned on.

The output of the constant current circuit 32 of the main power supply circuit section 30 is adjusted to have a predetermined voltage in the constant voltage circuit 33, and the voltage is applied to the terminal T31, contact type connector 300, and terminal T32 of the battery pack 100.

A method for supplying power from the adapter 1 to the portable radio telephone 200 in this embodiment will be described. In this embodiment, the power from the adapter 1 is supplied to the portable radio telephone 200 via the battery pack 100.

In the event that the power switch 201 of the portable radio telephone 200 is turned off and the portable radio telephone 200 is mounted on the adapter 1, as described above, only the constant current circuit 41 of the sub-power supply circuit section 40 is turned on, and the battery 102 of the battery pack 100 is charged with constant current of 120 mA supplied from the constant current circuit 41.

When the portable radio telephone 200 in its wait state is mounted on the adapter 1, only the constant

current circuit 41 of the sub-power supply circuit section 40 is turned on, the portable radio telephone 200 receives, through the battery pack 100, a current necessary for operations of the portable radio telephone 200 in the wait state from the constant current of about 120 mA output from the constant current circuit 41, and the other current flows into the battery 102 of the battery pack 100 as a charging current. The current necessary for operations of the portable radio telephone 200 in the wait state is switched from the current from the battery 102 of the battery pack 100 to the current from the constant current circuit 41 of the sub-power supply circuit section 40 of the adapter 1. When the portable radio telephone 200 in the wait state is mounted on the adapter 1, the switch 11 of the power supply section 10 is turned on and the hands-free circuit section 70 is rendered operative.

In the event that the portable radio telephone 200 which has been turned on and established a speech radio link is mounted on the adapter 1, the constant-current circuit 32 of the main power supply circuit section 30 of the adapter 1, the constant-current circuit 41 of the sub-power supply circuit section 40, and the switch 11 of the power supply section 10 are all turned on. The portable radio telephone 200 is supplied with power from the constant-voltage circuit 33 of the main power supply circuit section 30 and from the constant-current circuit 41 of the sub-power circuit section 40 through the battery pack 100, and the hands-free circuit section 70 is supplied from the power supply section 10. The power supplied to the portable radio telephone 200 is switched from the power from the battery 102 of the battery pack 100 to the power from the constant-voltage circuit 33 of the main power supply circuit section 30 of the adapter 1 and the constant-current circuit 41 of the sub-power supply circuit section 40.

If the portable radio telephone 200 is disconnected from the adapter 1 in this state, the power supplied to the portable radio telephone 200 is switched from the power from the constant-voltage circuit 33 of the main power supply circuit section 30 of the adapter 1 and the constant-current circuit 41 of the sub-power supply circuit section 40 to the power from the battery 102 of the battery pack 100. The switch 11 of the power supply section 10 is then turned off, and the hands-free circuit section 70 is rendered inoperative.

Consequently, the portable radio telephone 200 can freely be attached to and detached from the adapter 1, irrespective of the operational states of the portable radio telephone.

Next, the operation of the over-current detection/protection circuit 50 will be described.

The over-current detection/protection circuit 50 fulfils the following functions when the portable radio telephone 200 is in a communication state.

- a) The circuit 50 detects an abnormal amount of charging current due to the internal short circuit in

the battery pack 100 mounted on the portable radio telephone 200.

- b) The circuit 50 starts an abnormality monitoring timer after detecting the abnormal amount of current.

- c) If the abnormal amount of current flows when the abnormality monitoring timer stops, the constant-current circuit 32 of the main power supply circuit section 30 is turned off.

The operation of the over-current detection/protection circuit 50 will be described when the portable radio telephone 200 in the communication state is mounted on the adapter 1. If the portable radio telephone 200 is mounted on the adapter 1, the constant-current circuit 32 of the main power supply circuit section 30 is turned on, as described above. 5V-power is supplied to each section of the over-current detection/protection circuit 50 through the 5V regulator 51. A reset signal RE is supplied from a 4.4V detection circuit 52 to each section of the over-current detection/protection circuit 50. The 4.4V detection circuit 52 detects that an output of the constant-voltage circuit 33 of the main power supply circuit section 30 decreases down to 4.4V, and generates the reset signal RE which falls from high level to low level. Flip-flops 55 and 59 of the over-current detection/protection circuit 50 are reset by the fall of the reset signal RE, and a timer 57 is cleared by the fall of the reset signal RE.

If the charging current of the battery pack 100 abnormally increases, this increase is detected by an over-current detection circuit 53 for monitoring a voltage at both end of a resistor 31 arranged before the constant-current circuit 32 of the main power supply circuit section 30. The over-current detection circuit 53 usually outputs a low-level signal and outputs a high-level signal when it detects over-current. When the output signal of the over-current detection circuit 53 rises from low level to high level, a one-shot circuit 54 is triggered in synchronisation with this rise and generates a one-shot pulse. Since the flip-flop 55 is reset in the initial state, a set output Q of the flip-flop 55 is low in level, an AND circuit 56 is rendered inoperative, and a clock signal from a clock generator 63 is not supplied to a clock terminal CK of the timer 57. If the flip-flop 55 is set in response to the one-shot pulse from the one-shot circuit 54, the set output Q of the flip-flop becomes high level. The AND circuit 56 is thus rendered operable, and the clock signal generated from the clock generator 63 is supplied to the clock terminal CK of the timer 57. The timer 57, therefore, starts to operate. When the timer 57 stops, it outputs a high-level signal, and this high-level signal is supplied to an AND circuit 58. An output of the over-current detection circuit 53 is added to the other inputs of the AND circuit 58. If the over-current detection circuit 53 still detects over-current, the AND conditions of the AND circuit 58 are satisfied. The flip-flop 59 is thus set, and an inverted signal output from the flip-

flop 59 falls from high level to low level. The AND circuit 25 of the power control circuit section 20 rendered inoperative, an output of the AND circuit 25 changes from high level to low level, and the constant-current circuit 32 of the main power supply circuit section 30 is turned off.

If an output of the over-current detection circuit 53 falls to a low level when the timer 57 stops, the AND conditions of the AND circuit 58 are not satisfied and the flip-flop 59 is not set.

Therefore, an output of the AND circuit 25 of the power control circuit section 20 remains high in level, and the constant-current circuit 32 of the main power supply circuit section 30 is not turned off.

When the timer 57 stops, the one-shot circuit 54 is triggered by the fall of the high-level signal output from the timer 57, and the timer 57 is cleared by the one-shot pulse generated from the one-shot circuit through an OR circuit 61, or the flip-flop 55 is reset through an OR circuit 62, thereby preparing against the next over-current. After that, even though the portable radio telephone 200 is detached from the adapter 1, the above operation is repeated if the portable radio telephone 200 is mounted on the adapter 1 again, as long as the communication state continues.

If the portable radio telephone 200 is mounted on the adapter 1 when the portable radio telephone 200 is in the wait state or when the power switch 201 is turned off, the constant-current circuit 32 of the main power supply circuit section 30 is not turned on and accordingly the over current detection/protection circuit 50 does not operate.

The operation of the hands-free circuit section 70 will be described in detail, mainly referring to Figure

3. Terminals T61, T71, T81 and T91 of the hands-free circuit section 70 are connected to terminals T62, T72, T82 and T92 of the portable radio telephone 200 through the contact type connector 300, respectively. An audio reception signal supplied from the portable radio telephone 200 to the hands-free circuit section 70 appears at the terminal T92 of the portable radio telephone 200, and an audio transmission signal supplied from the hands-free circuit section 70 to the portable radio telephone 200 appears at the terminal T61 of the hands-free circuit section 70. Furthermore, a speaker signal, which is at a high level in a conversation mode for normal conversation and at a low level in a data transmission mode for data communication such as facsimile communication, appears at the terminal T82 of the portable radio telephone 200, and a hands-free signal, which is at a high level when hands-free calling is selected and at a low level when it is not selected, appears at the terminal T72 thereof.

The case where the hands-free calling is selected, the high level hands-free signal is generated at the terminal T72 of the portable radio telephone 200, and the high level speaker signal representing the

conversation mode is generated at the terminal T82 will be described.

A speaker pass switch 72 is turned on in response to the high level speaker signal generated at the terminal T81, and a data communicating switch 88 is turned off in response to the high level hands-free signal generated at the terminal T72. A transistor 85 is turned on and a transistor 84 is turned off, in response to the high level hands-free signal. The transistor 85 is turned on, accordingly, a speech switch 83 is turned on by turning on the transistor 85.

If the audio reception signal is generated at the terminal T92 of the portable radio telephone 200 and supplied to the T91 of the hands-free circuit section 70 through the contact type connector 300, the audio reception signal is amplified to a predetermined level by an amplifier 71, and supplied to a volume circuit 73 through the speaker pass switch circuit 72. As is evident from the following description, an output of a reception/transmission level comparing circuit 79 is high in level, a reception insertion loss changing switch 74 is turned on, and an output of the volume circuit 73 is greatly attenuated and supplied to a power amplifier 75. Therefore, the volume of a hands-free speaker to which an output of the power amplifier 75 is supplied through terminal Td, is decreased to such an extent that the bi-directional characteristics of conversation cannot be degraded.

The output of the amplifier 71 is partially supplied to an amplification rectifying circuit 77 as a reception monitor signal. The signal is amplification rectified and input to a plus terminal of the reception/transmission level comparator 79. The amplification rectifying circuit 77 is biased so that an input voltage of the comparator 79 becomes higher at the pulse terminal when neither an audio reception signal nor an audio transmission signal is supplied. If an audio reception signal having a predetermined level or more is input, an output of the comparator 79 becomes low in level, the switch 74 is turned off, and the gain of the reception system is increased. The output of the comparator 79 increases the gain of the amplification rectifying circuit 77 by turning off a gain varying switch circuit 76 of the circuit 77 and is caused to have hysteresis characteristics to prevent the reception mode from being easily changed to the transmission mode.

An audio transmission signal input from the hands-free microphone 700 is supplied to an amplifier 80 through a terminal Tc. The signal is amplified to have a predetermined level and then supplied to an insertion loss changing circuit 81. Since the output of the comparator 79 is still low in level, the transmission signal is greatly damaged by the circuit 81 and attenuated to such a level that the bi-directional characteristics of conversation is not degraded. The transmission signal is supplied to the terminal T61 through an amplifier 82 and a switch 83, and transmitted to the terminal T62 of the portable radio telephone

200 through the contact type connector 300.

The output of the amplifier 80 is partially supplied to an amplification rectifying circuit 78 as a transmission monitor signal. The signal is amplification rectified and input to a minus terminal of the reception/transmission level comparator 79. Since the reception signal is lost, the signal supplied to the plus terminal of the comparator 79 is quickly decreased in level, and the output of the comparator 79 is quickly inverted and becomes high in level. Since the switch 74 is thus turned on and the circuit 81 is turned off, the transmission signal is supplied to the terminal T61 at a normal level and transmitted to the terminal T62 of the portable radio telephone 200 through the contact type connector 300.

The case will be described where a facsimile apparatus serving as a data terminal is used. At the event, the hands-free signal of the terminal T72 of the portable radio telephone 200 becomes low in level, and the speaker signal of the terminal T82 becomes low in level.

The speaker pass switch 72 is turned off by the low level speaker signal of the terminal T81, and the data communicating switch 88 is turned on by the low level hands-free signal of the terminal T72. Further, the transistor 85 is turned off and the transistor 84 is turned on by the low level hands-free signal of the terminal T72. Furthermore, the switch 83 is turned off by turning off the transistor 85. A facsimile transmission signal input from the facsimile apparatus 600 through a terminal Tb is amplified by an amplifier 87 to have a predetermined level, supplied to the terminal T61 through the data communicating switch 88, and transmitted to the terminal T62 of the portable radio telephone 200 through the contact type connector 300.

A facsimile reception signal is input to a terminal T91, amplified by the amplifier 71 to have a predetermined level, and supplied to the facsimile apparatus 600 through a resistor 86 and terminal Tb.

In the above embodiment, the speaker 900 is externally attached to the adapter 1. However, the speaker 900 may be included in the adapter 1.

Figure 6 shows the appearance of the adapter including the speaker.

The adapter 1 is provided with a circuit board 2 including the power supply section 10, power control circuit section 20, main power supply circuit section 30, sub-power supply circuit section 40, overcurrent detection/protection circuit section 50, and hands-free circuit section 70. The circuit board 2 is provided with a connector 3 connected to the facsimile apparatus 600 serving as a data terminal. The connector 3 corresponds to the terminal Ta shown in Figure 1. The adapter 1 is connected to a car-mounting battery for applying a voltage of 13.7V through a line 4 and also connected to the hands-free microphone 700 through a line 5. A recessed portion 1a into which the portable radio telephone 200 is mounted, is for-

med on the upper portion of the adapter 1, and the contact type connector 300 for connecting the circuit section of the adapter 1 to that of the portable radio telephone 200 is formed on the bottom portion of the hole 1a.

The battery pack 100 is mounted on the back portion of the portable radio telephone 200, and an extendible antenna 202 is attached to the top of the battery pack 100.

When the portable radio telephone 200 is thrown into the recessed portion 1a of the adapter 1, the circuit sections of the portable radio telephone 200 and battery pack 100 are electrically connected to the circuit section of the adapter 1 through the contact type connector 300.

The portable radio telephone 200 will be described in detail.

As shown in Figure 7, a radio section 203 comprises a demodulator 231, a modulator 232, a power amplifier 233, a duplexer 234, and a synthesiser 235. The demodulator 231 demodulates a reception signal received from the base station through the antenna 202 and the duplexer 234. The reception signal contains control signals and an audio signal. The output of the demodulator 231 is supplied to a control signal processing section 267 through a switch circuit section 268, and also selectively supplied as audio reception signal to the hands-free circuit section 70 (shown in Figure 7) of the adapter 1 through the terminal T92 or to an ear piece 213 of the portable radio telephone 200 through an amplifier 215 under controls of the audio control section 269. The modulator 232 modulates control signals supplied from the control signal processing section 267 and audio signals selectively supplied from the hands-free circuit section 70 (shown in Figure 1) of the adapter 1 through the terminal T62 or from a mouth piece 214 of the portable radio telephone 200 through an amplifier 216. The power amplifier 233 amplifies a transmission signal output from the modulator 232. The duplexer 234 transmits a reception signal input through the antenna 202, to the demodulator 231, and transmits a transmission signal input through the modulator 232 and power amplifier 233, to the antenna 202. The synthesiser 235 is a channel selecting local generator to designate the frequency to be demodulated by the demodulator 231 and the frequency to be modulated by the modulator 232.

An audio control section 206 comprises a CPU 261, an oscillator/frequency-divider 262, an address decoder 263, a ROM 264, a RAM 265, a radio section controlling section 266, an audio section 267, a control signal processing section 268, an audio control section 269, a digital interface 270, and an interrupt controller 271.

In Figure 7, reference numeral 201 indicates a power switch; 207, an IDROM; 209, a power supply control section; 274, a data bus of, e.g. 8 bits; 273, an

address bus; and 272 a control bus.

The CPU 261 controls the whole of the audio control section 206, and the oscillator/frequency divider 262 supplies a clock to the CPU 261, 062 frequency divides the clock, and supplies the frequency divided clock to each section as a timing signal. The address decoder 263 outputs a predetermined operating signal from the CPU 261 to each section in response to an instruction signal. The ROM 264 stores various programs necessary for the operation of the CPU 261. The RAM 265 stores various types of data when the CPU 261 performs the processing operation. The radio section controlling section 266 controls the radio section 203 in response to the instruction of the CPU 261. For example, the radio section controlling section 266 designates a frequency to be designated by the synthesiser 235, an amplification factor at which the power amplifier amplifies transmission signals, and a degree of modulation at which the modulator 232 modulates the transmission signals. The radio section controlling section 266 also receives an asynchronous signal output from the synthesiser 235 to prevent an erroneous operation and a detection signal output from the power amplifier 233 and then supplies these signals to the CPU 261.

The control signal processing section 267 performs bit synchronisation and frame synchronisation with the control signal output from the switch section 268 extracts control data included in the control signal received from the base station, and sends control data to be transmitted to the base station to the switch section 268.

The audio control section 269 performs various types of controls of the audio paths. For example, the audio control section 269 controls the switch circuit 268 so that the signals output from the demodulator 231 are selectively applied to the amplifier 215, and so that the output of the amplifier 216 is selectively coupled to the input of the modulator 232.

When a user wishes to connect a facsimile machine to the portable radio telephone in order to transmit image data, the user enters a predetermined command on the operation panel 212. The command is applied to the CPU 261 through the digital interface 270. Responsive to the command, the CPU 261 controls the audio control section 269 so that it generates a speaker signal. The speaker signal becomes high in level in a conversion mode for normal conversation and low in level in a data transmission mode for data communication such as the facsimile communication.

When the user wishes to call by the hands-free operation, the user enters a predetermined command on the operation panel 212. The command is applied to the CPU 261 through the digital interface 270. Responsive to the command, the CPU 261 controls the audio control section 269 so that it generates a hands-free signal. The hands-free signal becomes high in level when the hands-free operation is selected and

low in level when it is not selected. The speaker signal and hands-free signal are transmitted through the terminals T82 and T72, respectively.

The digital interface 270 forms an interface between the audio control section 206 and operation panel 212. The interrupt controller 271 interrupts the CPU 261 in response to an interrupt instruction from each section.

The digital interface 270 generates a calling/waiting signal which becomes high in level in the communication state and low in level in the waiting state and outputs the calling/waiting signal to the terminal T42.

The power supply control section 209 generates a power-on signal which becomes high in level when the power switch is turned on and low in level when it is turned off, and supplies the power-on signal to the terminal T52.

In the embodiment described above, the communication state of the portable radio telephone may be defined as a state wherein the portable radio telephone has established a radio link for speech communication. In the state, a user may have a conversation with another party over the radio link. The communication state of the portable radio telephone may be defined as a state wherein a transmitter section such as the power amplifier 233 of the portable radio telephone is powered for transmission of signals.

As described above, according to the present invention, the portable radio telephone is detachably connected to the adapter through the connector connectable to at least the power line. When the portable radio telephone which is not in the conversation mode is connected to the adapter through the connector, only the first power supply circuit, enough to charge the chargeable battery of the portable radio telephone is turn on, and both the first power supply circuit and the second power supply circuit, enough for operation of the portable radio telephone are turned on in the communication state. Since, therefore, a cord for connecting the adapter and portable radio telephone is not needed, useless current flows from a power supply such as a car mounting battery for supplying power to the adapter, and a waste of the power supply such as the car mounting battery can be prevented.

Although an embodiment applied to a cellular radio telephone has been described, it will be apparent to those skilled in the art that the present invention may be easily applied to any kind of radio communication apparatus, for example, a cordless telephone and so on.

Whilst the foregoing description is directed to presently preferred embodiments, it will be apparent to those of ordinary skill that various modifications may be made within the scope of the appended claims.

Claims

1. A radio telephone apparatus comprising a portable radio unit (200) having receiving means (202, 234) for receiving radio frequency signals, demodulating means (231) coupled to the receiving means for demodulating the radio frequency signals into audio signals, an earpiece (213) coupled to the demodulating means for outputting the audio signals, a mouthpiece (214) for inputting speech signals, modulating means (232) coupled to the mouthpiece for modulating the speech signals into radio frequency signals, transmitting means coupled to the modulating means for transmitting the radio frequency signals (233, 202, 234), and an adapter unit (1) attachable to the portable radio unit, having a speaker (900), a microphone (700) and a hands-free circuit (70) coupled to the second contact type connector means, the speaker, and the microphone for controlling the level of signals output from the speaker in response to the level of signals input to the microphone, characterised by:
 - first computer means (T92, T62) on the portable unit and co-operating second connector means (T91, T61) on the adapter, whereby the hands-free circuit is activated in response to a contact between the first connector means (T92, T62) and the second connector means (T91, T61) in the event that the portable radio is attached to the adapter unit whilst communication is in progress.
2. A radio telephone apparatus according to claim 1 further characterised in that the hands-free circuit is not activated in response to a contact between the first connector means and the second connector means unless the portable radio unit is powered up or when it is attached to the adapter unit.
3. A radio telephone apparatus according to claim 1 or claim 2 further characterised in that the portable radio unit comprises first power supply means (40) for charging a rechargeable battery of the portable radio unit with electric power in the event that the portable radio unit being not in the communication state is connected to the adapter unit and second power supply means (30) for supplying the portable radio unit with electric power in the event that the portable radio unit being in the communication state is attached to the adapter unit, the power supply capacity of the second power supply means being larger than that of the first power supply means.
4. A radio telephone apparatus according to any preceding claim further characterised in that the adapter unit comprises a terminal (Tb) for connecting an external data device with the adapter, switch means (99) responsive to a control signal for connecting the terminal to the second contact type connector means, whereby a two-way data transmission path is established between the external data device and the portable radio unit when the portable radio unit is connected to the adapter unit.
5. An adapter unit (1) for use with a portable radio unit (200) coupled to the adapter unit and having a rechargeable battery (100) for supplying the portable radio unit with electric power, characterised by:
 - first power supply means (40) for charging the rechargeable battery with electric power in the event that the portable radio unit is not powered by the rechargeable battery when it is connected to the adapter unit; and
 - second power supply means (30) for supplying the portable radio unit with electric power in the event that the portable radio unit is powered by the rechargeable battery and in a communication state when it is attached to the adapter unit, the power supply capacity of the second power supply means being larger than that of the first power supply means.
6. An adapter unit according to claim 5, characterised in that the adapter unit comprises a hands-free circuit (700) for controlling the level of signals output from a speaker of the adapter unit in response to the level of signals input to a microphone of the adapter unit.
7. An adapter unit according to claim 6, characterised in that the hands-free circuit is activated in response to a connection between the adapter unit and the portable radio unit when it is in the communication state.
8. An adapter unit according to claim 6 or claim 7, characterised in that the hands-free circuit is not activated in response to a connection between the adapter unit and the portable radio unit unless communication is in progress.
9. An adapter unit according to any of claims 5 to 8, characterised in that the adapter unit comprises a terminal (Tb) for connecting an external data device with the adapter, switch means (88) responsive to a control signal for connecting the terminal to a first connector means, whereby the external data device and the portable radio unit in response to a contract between the first connector and a second connector of the portable radio

unit in the vent that the portable radio unit is attached to the adapter unit.

5

10

15

20

25

30

35

40

45

50

55

11




Fig.1.




Fig.2.




Fig.3.




Fig.4.




Fig.5.





Fig.6.




Fig. 7.